

# OCI® Multipurpose Aerosol Spray Paint



## Technical Data Sheet

**OCI Multipurpose** spray paint presents a wide spectrum of brilliant jobs with a professional finish. The advanced formulation provides outstanding resistance to peeling, cracking, chipping, and color fading caused by all weathering conditions.

### Physical Data

#### Acrylic based paint

Drying time(Tack free)	≤10min
Hard dry	≤60min
Viscosity	12-14 sec. (Cup 4#/23±2°C)
Solid content	≥20%
Coverage	0.6 to 1.5 m <sup>2</sup> / can
Package:	300 ml/can, 12 cans/carton

### Directions

1. Shake can thoroughly for at least 30 seconds until the metal agitator (mixing ball) begins to rattle.
2. Make sure the surface is clean, dry, and free of grease. Do not spray over loose paint. Remove loose paint with wire brush or sand paper before spraying.
3. Hold can approximately 12 inches (30cm) from the surface. To obtain smooth finish, spray 2 or more thin coats in a steady side to side motion, preferably 10 minutes interval between each spray.
4. Dry to touch in approximately 20 minutes. Allow more drying time at cooler temperatures.
5. Store at room temperature.

### IMPORTANT:

After spraying, clean the valve by turning the can upside down and pushing the spray head for approximately 4 seconds. If the valve clogs, pull out the spray head and rinse it in solvent such as paint thinner.

# OCI® Multipurpose Aerosol Spray Paint



## Technical Data Sheet

### Precautions

Contents are extremely flammable and under pressure. Keep away from heat, flame, spark and any other source of ignition. Store in cool and dry places. Do not clash, puncture, or incinerate the can. Keep out of the reach of children.

### Storage

- Store in dry and cool place between +5°C to 25°C.
- Shelf life of 24 months.

Every endeavor has been made to ensure that the information given herein is true and reliable but it is given only for the guidance of our customers. The company cannot accept any responsibility for loss or damage that may result from the use of the information, due to the possibility of variations of processing or working conditions and of workmanship outside our control. Users are advised to confirm suitability of this product by their own tests.